



Coach Style Lantern

The CSL is a high performance utility grade LED luminaire with a traditional styling allowing it to compliment well established or historical settings.

The CSL lantern has versatile mounting options and incorporates features that promote long service life and easy maintenance.

Utilizing a modular LED approach the CSL is scalable in output and it's also flexible with four standard light distributions and several custom distributions available.

For most updated performance & ordering information visit us at amerlux.com/avista.

Features & Specs

- Up to 121 LPW
- 3,000K, and 4,000K color temperatures
- Up to 9,630 Lm
- IP66 rated sealed optics
- Automatic AC incoming voltage sensing 120V-277V
- · Easy install, using post-top or arm mounting
- Integrated 3-pin and 7-pin receptacle option available
- · Series wired 20kV/10kA surge protector
- DLC listed

Distributions


- Type II (T2)
- Type III (T3)
- Type IV (T4)
- Type V (T5)
- Custom (TC)





CSL-A





CSL-A





Cast aluminum roof with rotatable photocell receptacle and cover.



IP66 sealed LED modules (1-4 modules available)



Die cast aluminum base with black anodized stainless steel hardware

Light Distribution / Typical Lumens

LED Module	Type II	Type III	Type IV	Type V
1 Module	2,275 lm	2,295 lm	2,220 lm	2,318 lm
2 Module	4,443 lm	4,485 lm	4,339 lm	4,531 lm
3 Module	6,647 lm	6,702 lm	6,490 lm	6,778 lm
4 Module	8,735 lm	8,803 lm	8,528 lm	8,907 lm
Polar Plot				

Company Certifications:























