

AO25 SERIES LED LUMINAIRE

U.4.1.16

AO25 Series
LED

DESCRIPTION:

Lighting for exterior retail, commercial and hospitality environments. The AO25 Series consists of a decorative acorn combined with one of several styles of cast aluminum fitters.

LED LUMINAIRE:

Multiple LED systems available with convection cooled driver, options for intensity, distribution and color. They operate with over voltage and short circuit protection and automatic voltage sensing for 120 to 277v input. (See next page for LED availability)

- 50,000+ hours of operational life
- Warm 3000K, neutral 4000K, or cool white 5000K color
- Dimmable (controller by others)
- Suitable for wet locations

ETL listed, suitable for wet locations.

INSTALLATION:

The luminaire will mount to a 3" OD post or tenon with 5/16" black oxide coated stainless steel set screws to ensure a solid connection. The diffuser will be held to the fitter by (4) 1/4"-20" black oxide coated stainless steel captive set screws.

DIFFUSER CHOICES:

- Clear Textured Polycarbonate (**PC-CL**)
- White Textured Polycarbonate (**PC-WH**)
- Clear Textured DR Acrylic (**DR-CL**)

FINISH


Premium quality thermoset polyester powdercoat for a durable finish in the following:

- BLK** - Satin Black
- CLB** - Classic Bronze
- GBZ** - Gloss Textured Bronze
- GRN** - Green
- GTB** - Gloss Textured Black
- TBK** - Textured Black
- TGR** - Gloss Textured Green



PROJECT:

TYPE:



Ordering Information:

Model	Diffuser Material-Color	LED System	Light Distribution	Order Code	Finish	Option
D131/AO25 D133/AO25 D134/AO25 D135/AO25 D136/AO25 D137/AO25 D138/AO25 D139/AO25	PC-CL PC-WH DR-CL	AVI LSK VLE	AS SY	3H,4H,5H 3L,4L,5L	BLK CLB GBZ GRN GTB TBK TGR Custom	BB BB-FW CFIN PCL SR

See next page for more complete ordering options




5 year limited warranty
AMERLUX LED



Part String


Example: D131/AO25PC-CL/AVI-SY-3H/BLK

LED Options (bold indicates ordering code)



LED System	Light Distribution	Code	CCT	CRI	Light Engine Lumens	Nominal Input Power	
AVI	SY (Symmetric)	3H	3,000K	80	4,450 lm	60W	
		4H	4,000K	80	5,100 lm		
		5H	5,000K	70	5,870 lm		
	AS (Asymmetric)	3H	3,000K	80	4,410 lm		41W
		4H	4,000K	80	5,050 lm		
		5H	5,000K	70	5,810 lm		
	SY	3L	3,000K	80	2,940 lm	41W	
		4L	4,000K	80	3,460 lm		
		5L	5,000K	70	4,070 lm		
	AS	3L	3,000K	80	2,910 lm		41W
		4L	4,000K	80	3,420 lm		
		5L	5,000K	70	4,030 lm		


Example: **D131/AO25/PC-CL/AVI-SY-3H/BLK**



LED System	Light Distribution	Order Code	CCT	CRI	Light Engine Lumens	Nominal Input Power	Dimmable
VLE	SY (Symmetric)	3H	3,000K	80	5,600 lm	80W	0-10V
		4H	4,000K	80	5,700 lm		
		5H	5,000K	70	6,000 lm		
	AS (Asymmetric)	3H	3,000K	80	4,200 lm	60W	
		4H	4,000K	80	4,300 lm		
		5H	5,000K	70	4,500 lm		
	SY	3L	3,000K	80	3,000 lm	40W	
		4L	4,000K	80	3,300 lm		
		5L	5,000K	70	3,600 lm		
	AS	3L	3,000K	80	2,200 lm	30W	
		4L	4,000K	80	2,500 lm		
		5L	5,000K	70	2,800 lm		

Example: **D131/AO25PC-WH/VLE-SY-3H/BLK**

Photometry



AO25/PC-CL/LSK-SY-3H
 Luminaire Lumens = 3,469
 Scale: 1 Unit = 12 Ft.
 Mounting Height = 12.00 Ft.