


POLE ACCESSORIES


U.7.11.14




PCL (120v only)
PCL-MULTI (208v thru 277v)
 Dusk to dawn button type photocell for automatic switching of luminaires. Black polycarbonate housing. See Accessory orientation guide to specify location.




FPH-4 or FPH-5
 Extruded aluminum holder for 1" OD flag poles. The flag pole holder is set at 45° angle and welded to a field rotatable and height adjustable collar. Available for 4" OD and 5" OD non-tapered pole.




LR
 Cast aluminum decorative ladder rest slip fits 3" OD pole or tenon. Integral 3" OD cast tenon provided for luminaire mounting (not designed to support ladder or other objects).



Pole Finials
 Decorative post top finials for use with side mount brackets or when signs are installed without luminaires. Finials attach to 3" OD pole or tenon with 3 set screws.




Street Signs
 Street name signs, informational and directional signs along with mounting systems are available to complete any street scape. See "STREET SIGNS" page for details.




Direct Burial Option
 Direct burial extensions are available for most Cast / Extruded poles. Contact factory for details.


Banner Arms



Fixed position banner arm for 4" or 5" OD poles (can be used on tapered poles). Aluminum 3/4" NPT coupling is permanently welded at the specified location. 24" extruded aluminum banner arm is removable.



Single or double field rotatable arms for 4" OD non-tapered poles. 3/4" NPT x 24" long extruded aluminum arm threads onto cast collar that clamps to pole with (2) 3/8" dia. stainless steel socket head screws. Other lengths available.





Single or double field rotatable arms for 5" OD non-tapered poles. 3/4" NPT x 24" long extruded aluminum arm threads onto cast collar that clamps to pole with (2) 3/8" dia. stainless steel socket head screws. Other lengths available.


Finish on all arms will match posts

GFCI


The 20 amp, 125 volt, ground fault circuit interrupter duplex receptacles are recessed (RM) or surface mounted (SM) to the post or base. The receptacles shall have a cast aluminum UL listed cover. The GFCI-WWIU has a cover that is suitable for wet locations while in use. The receptacle and cover shall mount to an outlet opening, in the post shaft or base, with a gasket and stainless steel screws. Finish will match pole.



GFCI-RM



GFCI-SM



GFCI-RM-WWIU