

D623

LED Luminaire



PROJECT:

TYPE:

Features

The D623 Luminaire is a versatile six sided post top lantern that is best suited for poles under 10' in height. Powered by the Amerlux patented AVISTA® LED system with options for intensity, distribution and color.

Product Overview

Wattage:	30W, 44W
Lumen Output:	up to 6099 lm; up to 143 lm/W
Color Temp:	2700K, 3000K, 4000K 1900K (<i>Nightscape</i>)
Dimming:	0-10V dimming Manual onboard dimming option available
EPA:	1.81



D623

Certifications



Fixture Summary

Installation:

The luminaire will mount to a 3" OD post or tenon with 5/16" black oxide coated stainless steel set screws to ensure a solid connection.

Electrical:

- Over voltage and short circuit protected driver
- Series connected 10kV/20kA surge protector
- Automatic AC incoming voltage sensing (120V-277V)
- 347V/480V option consult factory
- 0-10V dimming
- Optional Socket only version available, consult factory

Lenses:

- Clear Acrylic
- Textured Acrylic

Distribution:

- Symmetric
- Asymmetric
- Street Optic

CCT, CRI:

- 2700K, 80CRI
- 3000K, 70CRI
- 4000K, 70CRI
- 1900K, 52CRI (*Nightscape*, see pg 4)

Power Level:

(see performance chart for output)

- 30W
- 44W

L70:

72,000+ hrs.

Finish:

Durable thermoset polyester powdercoat finish in the following:

- Satin Black
- Classic Bronze
- Gloss Textured Bronze
- Green
- Gloss Textured Black
- Textured Black
- Gloss Textured Green

Accessories:

- Dusk-to-dawn button type photocell
- Controls Capable Harness
- Integrated 7-pin NEMA receptacle
- Optional onboard field selectable output switch for dimming
- Wireless control option

ETL listed, suitable for wet locations.



D623

LED Luminaire



PROJECT:


TYPE:

Ordering Information


D623		AVI-G3-U					
1	2	3	4	5	6	7	8
1 Model	2 Lens	3 LED System	4 Light Distribution	5 CCT	6 Power Level	7 Finish	8 Accessories
D623	CA clear acrylic TA textured acrylic	AVI-G3-U Avista light engine, multi-fit model	SY symmetrical AS asymmetrical SO street optic	27 2700K 30 3000K 40 4000K NS 1900K (Nightscape, see pg 4 for details)	P1 (30W) P2 (44W) 120V-277V auto-sensing driver is standard. Consult factory for 347V/480V option.	BLK satin black CLB classic bronze GBZ gloss textured bronze GRN green GTB gloss textured black TBK textured black TGR gloss textured green CSTM custom	PCL dusk-to-dawn button type photocell (not available for use with CCH) CCH controls capable harness (not available for use with PCL or FSO) 7P fixture integrated 7-pin NEMA receptacle (in place of finial, to allow installation of a wireless control node for operation on the SmartSite or other control platform, not available for use with FSO) FSO field selectable output option to allow manual dimming (not available for use with CCH or 7P) Consult factory for SmartSite integrated wireless control option (SSINT-1)

Please Note: Fixture is available with optional Medium base (MDO) or Mogul base (MGO) socket only. Consult factory for details.

Product Details



Avista Light Engine



AVI-G3

Weight: 6.2 - 6.6 lbs*

* Weight varies with Power output due to variances of the driver.



Delta Intelligent Building Technologies

178 Bauer Drive, Oakland, NJ 07436 • P: 973-882-5010 F: 973-882-2605 • amerlux.com
Amerlux reserves the right to change details that do not affect overall function and performance.
LIT-E0050 • 05/09/25 • Page 2 of 4

PROJECT:

TYPE:

Performance Data - Engine Only


Multiplying Factors: (Multiplying Factor is based on 3000K IES file on website)

CCT:	1900K (NS)	2700K	3000K	4000K
Factor:	0.85	1.0	1.05	1.05


Model		CCT	Power Level	System Watts	LED Engine Lumens	LED Engine LPW
AVI-G3-U	SY	27	P1	30	3651	122.9
		30			4034	135.8
		40			4246	143.0
		NS			3445	116.0
	AS	27			3505	118.0
		30			3872	130.4
		40			4076	137.2
		NS			2859	96.0
	SO	27			3296	111.0
		30			3579	120.5
		40			3883	130.7
		NS			3056	102.9
	SY	27	P2	44	5245	119.2
		30			5794	131.7
		40			6099	138.6
		NS			4948	113.0
	AS	27			5035	114.4
		30			5562	126.4
		40			5855	133.1
		NS			4107	94.0
	SO	27			4654	105.8
		30			5141	116.8
		40			5412	123.0
		NS			4390	100.5

Approximate lumens delivered from raw light engine.


Light Distribution Types



SY Type V



AS Type IV




SO Type III

PROJECT:


TYPE:

Spectral Power Distribution




Nightscape (NS) Technology

- Unique spectral distribution that delivers highest flux while emitting <2% light of blue.
- The Nightscape (*low blue*) Avista is powered by Luxeon 3030 HE Plus which delivers high efficacy and superior life span.



Blue radiation (microWatt, 400-500nm) per lumen



Blue radiation per lumen

