


**WARNING - RISK OF FIRE AND ELECTRICAL SHOCK. FIXTURE MUST BE INSTALLED BY A QUALIFIED ELECTRICIAN ONLY. FIXTURE IS INTENDED FOR INSTALLATION IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE, LOCAL AND FEDERAL SPECIFICATIONS. DISCONNECT POWER AT ELECTRICAL PANEL BEFORE SERVICING.
RETAIN THESE INSTRUCTIONS FOR MAINTENANCE REFERENCE.**

Pre-installation Note:




Supplied by Others: - (2) 4" Octagonal J-Box



Install junction boxes - The junction boxes should be installed flush with ceiling plane as shown. This will ensure the canopy cover sits flush with the ceiling when install is finished.





See below for proper location of mounting points/ locations for junction boxes.

1: Install Remote Driver Box*



*Driver Box size, shape & connection location may vary depending on fixture length and wattage. Most common box shown.


2: Install Feed Canopy Kits (Powered Aircraft Cable with 5" Canopy)




**Make sure to note which suspension point is positive (red) and negative (black).

Repeat steps A thru C for second suspension point.

Suspension Points:




Example of Continuous Rows





3: Mounting Fixture(s)



When fixture is removed from box **DO NOT** remove protective sleeve to protect from dust and construction debris.



Repeat steps B thru E for second suspension point.




Finally, remove protective sleeve(s) **ONLY** after **ALL** construction and finishing has been completed.



4: Joining Fixtures

(Only proceed when ALL fixtures in the row are hung, leveled & protective sleeves have been removed.)



Maintenance

- If fixture is not working properly, contact Amerlux Warranty for replacement.
- Do NOT attempt to repair. Any fixture disassembly will void warranty.
- Prior to ANY work, touch metal on fixture to discharge any buildup of static electricity

To take down fixture, use steps below. To install replacement follow section 3 above.

