

Grüv® 4"

High Efficiency Perimeter Cove

Recessed Linear LED



Features

Designed to provide high-performance, visually comfortable, high efficient comfortable perimeter ambient lighting with a 4" aperture for commercial and office environments. Featuring a choice of 2.5" or 4" regress options and ceiling interface options, Gruv4 HE Cove is an effective and aesthetically pleasing way of lighting space perimeters.

Product Overview

Type:	Recessed Lens Direct
Wattage:	5W/ft, 10W/ft (other wattages available see p2)
Lumen Output:	3,794 max; 100.1 Lm/W (10W, 4ft fixture)
Color Temp:	2700K, 3000K, 3500K, 4000K
CRI:	83 typ. or 90+ typ
Dimming:	0-10V, 1% dimming (standard) Lutron LDE1 Hi-lume® 1% Soft-On/Fade-to-Black DALI dimming, 1% dim



PROJECT:

TYPE:

Fixture Summary *(see following pages for more information)*

Ceiling Types

9/16"	15/16"	Gyp Board	Millwork
Yes	CF*	Yes	Yes

*Consult factory

Performance Chart

Wattage Per Foot	Delivered Lumens	LPW	Color Temp
5	2,148	107.0	3500K
10	3,794	100.1	3500K

Data is based on 3500K-83 IES files available on website

Data is based on 4' fixture with performance lens

Electrical Data

Wattage Per Foot		4'		8'	
		System Watts	Amps	System Watts	Amps
5	120V	22.3	0.18	41.9	0.35
	277V	22.9	0.09	41.6	0.16
10	120V	42.1	0.30	84.2	0.70
	277V	41.5	0.15	83.0	0.30

Electronic multi-volt (120-277VAC), constant current LED driver



Grüv® 4" HE Perimeter Cove

Recessed Linear LED



PROJECT:

TYPE:

Specifications

Application

Commercial and retail recessed perimeter cove ambient lighting.

Construction

Heavy gauge steel upper housing is secured to aluminum extruded trim rails. Die-formed, cold-rolled steel internal components and external mounting brackets. Numerous configurations accommodate most architectural ceiling conditions. Die formed steel cove walls - powder coat painted.

Optical

All lenses are snap-in, extruded acrylic, with a maximum length of 8'. Amerlux's proprietary acrylic lens provide excellent transmission while effectively concealing source image.
PL - Performance Lens provides high efficiency with controlled lens surface brightness (standard).
DL - Designer Lens provides flat even glow on lens. Best when lens is in direct or constant view. Such as vertical wall mounted.

LED

Amerlux's boards and patented connector design with brand name LEDs enables Amerlux fixtures to have excellent thermal management and offer a 5 year warranty. Our LED binning is within 3 MacAdam ellipse. Boards are configured for maximum flexibility resulting in even illumination no matter the fixture layout. LED boards are easily replaced in the field with just a Phillips screw driver.

Color Temperature Options: 2700K, 3000K, 3500K, 4000K

CRI: 83 typical, 90+ typical

R9: 16 @ CRI 83

R9: >50 @ CRI 92

Life: 50,000+ hr., > 70% of initial lumens (L70)

Electrical

Wiring: Supply wires are easily accessible through access plate on top of fixture.

WHIP: Optional factory installed 6' Greenfield whip (18/5 conductor) simplifies installation.

Standard Wattage: 5W/ft, 10W/ft.

Optional Wattages: 3W/ft, 4W/ft, 6W/ft, 7W/ft, 8W/ft, 9W/ft. (3W & 4W have a minimum length of 4'). For other wattages consult factory. Emergency circuit via remote inverter or auxiliary emergency power supply (by others).

This product complies with IEEE C62.41 for surge endurance up to 2.5KV. Amerlux® recommends using additional surge protection with this unit (supplied by others), surge and over voltage damage is not covered under warranty.

EMC-PF - Emergency circuit requires power feed to be located in last fixture section for continuous runs. For other locations consult factory. Not available for individual (IND) configuration.

PF - Extra power feed for additional circuiting. Not available for individual (IND) configuration.

Finish

HW - High reflectance, matte white powder coat paint. Baked on finish for maximum durability and color stability.

Configurations/Lengths

IND - Individual fixtures are made of single standard lengths of 2 ft to 8 ft (in 1' increments). These are stand alone fixtures with matching End Caps, supplied with the mounting hardware. Lengths less than 4' may have restrictions based upon wattage, lengths, drivers or other options.

CON - Continuous runs, > 8', specified to nearest whole foot length in 1' increments. Runs made from standard lengths have End Caps at the beginning and end of run. Runs > 60' may require second power feed. Each Housing has factory installed alignment pins. Mating fixtures are easily aligned and joined with "catch and latch" mechanisms out of sight, on top of the Housing. Wiring is made fast and positive with molded quick connectors.

CUS - Custom made to measure runs are made to nearest 1/8" of customer supplied field measurements or drawings. Custom lengths use the same hardware for hairline joining.

PXX - Standard Patterns consist of 90° corners with standard lengths (4' to 8' in 1' increments), continuous runs or made to measure lengths. Depending upon complexity of the pattern drawings may be required from the Customer. If ordering please give overall lengths.

A'-B'-PLL - L Left - (1) 90° Corner 2 segments. Specify overall segments: A' & B'

A'-B'-PLR - L Right - (1) 90° Corner 2 segments. Specify overall segments: A' & B'

A'-B'-PR - Rectangle - (4) 90° Corners joining 4 segments. Specify overall segments: A' & B'

A'-B'-C'-PU - U shape - (2) 90° Corners joining 3 segments. Specify overall segments: A', B', & C'

A'-B'-C'-PZ - Z shape - (2) 90° Corners joining 3 segments. Specify overall segments: A', B', & C'

See page 8 for layouts.

Mounting

Intended for use in gypsum board, 9/16" Tee grid and Screw Slot, and millwork ceilings. Wall mounting J-Molding details available. For individual, continuous row, or pattern applications.

Please note - fixtures to be installed before gypsum board ceiling.

GRUV4-HE-J/GB-COVE - J mold/gyp trimless, plastered in ceiling - J Channel wall side

GRUV4-HE-J/GRID-COVE - J mold/grid, in 9/16" Screw Slot or Flat Tee ceilings - J Channel wall side

GRUV4-HE-J/FLG-COVE - J mold/flange - J Channel wall side

Certifications

Approved to UL standards for damp locations as tested by CSA Intended for indoor use only
Chicago Plenum (CCEA) optional

Warranty

Amerlux's 5 year limited warranty. Please consult Amerlux website for details.

Grüv® 4" HE Perimeter Cove


Recessed Linear LED

amerlux
A Delta Group Company


PROJECT:

TYPE:


GRÜV4-HE-J/GB-COVE (j-mold/gyp board trimless)



GRÜV4-HE-J/GRID-COVE (j-mold/grid mount)



GRÜV4-HE-J/FLG-COVE (j-mold/flange)



Grüv® 4" HE Perimeter Cove

Recessed Linear LED



PROJECT:

TYPE:


GRUV 4" PATTERNS:

Standard Patterns


All corners are standard 90°, standard length legs.
Use standard lengths: 4' min to 8' in 1 foot increments.
Continuous runs must be the same length in pairs for closed configuration.

Custom Patterns

Please provide drawings of your configuration.
Made to Measure: +/- 1/8", consult factory.
PC - custom pattern, please provide drawings and consult factory



Gruv 4 Lens
Mitered Lens




PLL - L Left, (2) straights + (1) 90° corner, leg right

PLR - L Right, (2) straights + (1) 90° corner, leg left

Provide overall lengths: A' & B'


Nomenclature: A-B-PLL A-B-PLR



PR - Closed Rectangle, (4) straight lengths + (4) 90° corners

Provide overall lengths: A' & B'


Nomenclature: A-B-PR



PU - Open U, (3) straight lengths + (2) 90° corners

Provide overall lengths: A', B' & C'

Nomenclature: A-B-C-PU



PZ - Open Z, (3) straight lengths + (2) 90° corners

Provide overall lengths: A', B' & C'

Nomenclature: A-B-C-PZ

Grüv® 4" HE Perimeter Cove

Recessed Linear LED



PROJECT:

TYPE:

FIXTURE DATA: (Complete photometric data (.ies format) available upon request)

MULTIPLYING FACTORS: (Multiplying Factor is based on 3500K-83 120V IES file on website)

Wattage:	3W	4W	5W	6W	7W	8W	9W
Factor:	0.63	0.82	1.0	1.17	1.34	1.50	1.64


CCT-CRI:	2700K-83	3000K-83	3500K-83	4000K-83	2700K-90+	3000K-90+	3500K-90+	4000K-90+
Factor:	0.91	0.96	1.0	1.01	0.80	0.84	0.88	0.89

GRÜV 4" HE PERFORMANCE LENS 5W 3500K 4FT

Total Watts: 20

Total Lumens: 2,148

Source: 120 White LED's



ZONAL LUMEN SUMMARY

Zone	Lumens	%Fixt
0-40	1074	50.0
0-60	1769	82.4
0-90	2148	100.0
90-180	0	0.0

Luminaire Efficacy = 107.0 lm/w

COEFFICIENTS OF UTILIZATION

RC	70	50	80	30	10
RW					
RCR					
0	2497	2497	2497	2497	2497
1	2292	2204	2125	2053	2053
2	2093	1939	1811	1703	1703
3	1915	1718	1562	1437	1437
4	1760	1533	1364	1233	1233
5	1625	1379	1204	1073	1073
6	1505	1249	1073	945	945
7	1400	1138	965	842	842
8	1307	1043	874	756	756
9	1224	961	797	684	684
10	1151	890	731	623	623


Note: Values expressed as Lumens delivered to the task surface.

GRÜV 4" HE PERFORMANCE LENS 10W 3500K 4FT

Total Watts: 38

Total Lumens: 3,794

Source: 120 White LED's



ZONAL LUMEN SUMMARY

Zone	Lumens	%Fixt
0-40	1899	50.1
0-60	3126	82.4
0-90	3795	100.0
90-180	0	0.0

Luminaire Efficacy = 100.1 lm/w

COEFFICIENTS OF UTILIZATION

RC	70	50	80	30	10
RW					
RCR					
0	4412	4412	4412	4412	4412
1	4049	3894	3754	3628	3628
2	3697	3427	3201	3009	3009
3	3384	3035	2761	2540	2540
4	3110	2709	2411	2180	2180
5	2871	2437	2128	1897	1897
6	2660	2207	1897	1672	1672
7	2474	2011	1705	1488	1488
8	2310	1844	1545	1337	1337
9	2164	1699	1409	1210	1210
10	2034	1573	1292	1103	1103

Note: Values expressed as Lumens delivered to the task surface.

Grüv® 4" HE Perimeter Cove

Recessed Linear LED



PROJECT:

TYPE:

FIXTURE DATA: (Complete photometric data (.ies format) available upon request)

MULTIPLYING FACTORS: (Multiplying Factor is based on 3500K-83 120V IES file on website)

Wattage:	3W	4W	5W	6W	7W	8W	9W
Factor:	0.63	0.82	1.0	1.17	1.34	1.50	1.64

CCT-CRI:	2700K-83	3000K-83	3500K-83	4000K-83	2700K-90+	3000K-90+	3500K-90+	4000K-90+
Factor:	0.91	0.96	1.0	1.01	0.80	0.84	0.88	0.89


GRÜV 4" HE DESIGNER LENS 5W 3500K 4FT

Total Watts: 20

Total Lumens: 1,777

Source: 120 White LED's

LTL# 11665872.27



ZONAL LUMEN SUMMARY

Zone	Lumens	%Fixt
0-40	794	44.7
0-60	1393	78.4
0-90	1776	100.0
90-180	0	0.0

Luminaire Efficacy = 88.6 lm/w

COEFFICIENTS OF UTILIZATION

RC	70	50	80	30	10
RW					
RCR					
0	2066	2066	2066	2066	2066
1	1880	1802	1732	1668	1668
2	1706	1571	1458	1362	1362
3	1553	1379	1244	1134	1134
4	1421	1223	1076	962	962
5	1306	1094	942	829	829
6	1207	986	834	725	725
7	1120	895	746	640	640
8	1043	817	672	571	571
9	976	751	610	514	514
10	916	694	558	467	467

Note: Values expressed as Lumens delivered to the task surface.


GRÜV 4" HE DESIGNER LENS 10W 3500K 4FT

Total Watts: 38

Total Lumens: 3,127

Source: 120 White LED's

LTL# 11665872.28



ZONAL LUMEN SUMMARY

Zone	Lumens	%Fixt
0-40	1395	44.6
0-60	2451	78.4
0-90	3127	100.0
90-180	0	0.0

Luminaire Efficacy = 82.5 lm/w

COEFFICIENTS OF UTILIZATION

RC	70	50	80	30	10
RW					
RCR					
0	3636	3636	3636	3636	3636
1	3310	3172	3048	2936	2936
2	3002	2764	2565	2396	2396
3	2732	2427	2188	1995	1995
4	2500	2151	1892	1692	1692
5	2298	1924	1657	1458	1458
6	2123	1734	1467	1274	1274
7	1970	1573	1311	1125	1125
8	1835	1437	1182	1004	1004
9	1716	1320	1073	904	904
10	1611	1220	981	820	820

Note: Values expressed as Lumens delivered to the task surface.

Grüv® 4" HE Perimeter Cove

Recessed Linear LED



PROJECT:

TYPE:

DIMMING COMPATIBILITY:

Amerlux® Gruv fixtures are compatible with all major dimming protocols prevalent in the United States. Please see below for general compatibilities and wiring diagrams. Amerlux recommends testing your unique dimming configuration as the exact full configuration (Dimmer, Fixture Quantity, Voltage, etc) may affect dimming performance.

--- NOTE: INFORMATION BELOW IS FOR WIRED DIMMERS ONLY. FOR WIRELESS DIMMERS, CONSULT FACTORY ---


0-10V - DIMMING (Standard)

Integrates into a variety of building management and daylighting controls

Notes:

- 120V or 277V*
- Dims down to 1% light output
- Requires interface to turn off power to driver
- Consult Dimming manufacturer for installation instructions - DO NOT SHARE NEUTRALS!

0-10V Wiring Diagram



Compatible Dimmers†:

Wall Box

Lutron:

Diva - DVSTV
Maestro - MS-Z101
Nova-T - NTSTV-DV

Wattstopper:

ADF-120277

Leviton:

Renoir II

Center System

Lutron Grafikk Eye with GRX-TV1 Interface

LUTRON LDE1 DIMMING

Integrates into Lutron EcoSystem building management

Notes:

- 120VAC or 277VAC*
- Dims down to 1% Soft-On/Fade-to-Black
- EcoSystem Control
- Consult Dimming manufacturer for installation instructions - DO NOT SHARE NEUTRALS!

Compatible Dimmers†:


Lutron ECO System

Pow Pak Dimming Modules
Energi Savr Node
Grafik Eye QS/Homeworks
QS Control Unit
Quantum Hub
Homeworks QS/My Room

Central System

Lutron EcoSystem
compatible controls

Lutron LDE1 (HILUME-H-ECO) EcoSystem Digital Control Wiring Diagram



Notes:

* Driver is 277VAC dimmable with appropriate dimmer (by others). All provided wiring diagrams show 120VAC wiring colors and method. Please refer to 277VAC dimmer installation instructions for 277VAC wiring diagrams.

† The absence of a dimmer from the lists above does not imply incompatibility. Please consult factory for compatibility inquiries.

Grüv® 4" HE Perimeter Cove

Recessed Linear LED



PROJECT:

TYPE:

DIMMING COMPATIBILITY:

Amerlux® Gruv fixtures are compatible with all major dimming protocols prevalent in the United States. Please see below for general compatibilities and wiring diagrams. Amerlux recommends testing your unique dimming configuration as the exact full configuration (Dimmer, Fixture Quantity, Voltage, etc) may affect dimming performance.

--- NOTE: INFORMATION BELOW IS FOR WIRED DIMMERS ONLY. FOR WIRELESS DIMMERS, CONSULT FACTORY ---

DALI - DALI DIMMING 120V-277V

Digital control protocol allows individual fixture control

Notes:

- 120VAC - 277VAC*
- Dims down to 1% light output in most cases

Compatible Dimmers†:


Wall Box

Leviton CD250 Controller

Center System

Dynalite
Fifth Light

DALI Wiring Diagram



Notes:

* Driver is 277VAC dimmable with appropriate dimmer (by others). All provided wiring diagrams show 120VAC wiring colors and method. Please refer to 277VAC dimmer installation instructions for 277VAC wiring diagrams.

† The absence of a dimmer from the lists above does not imply incompatibility. Please consult factory for compatibility inquiries.