



LUMINAIRE ACCESSORIES

U.4.10.19

Reflectors and Shields




FDR
(Faceted Downlight Reflector)




LL (Light Lid)
Perforated aluminum reflector minimizes light to the upper hemisphere, while providing an aesthetically pleasing glow to the top of the diffuser. Consult Factory.

SLL (Solid Light Lid)
Solid aluminum reflector
Consult Factory.


Both models are limited to use on the following fixture series : **AO28, ARP23, D730AO, D730ARP**



TOP VIEW



HSS90




HSS180

HSS-90 (90 degree cutoff)
HSS-180 (180 degree cutoff)
House side shields are available to cutoff all direct light through certain horizontal angles. Both models clamp around the socket and are designed to be positioned in the field after installation of the fixture. If ordering for a retrofit application, the socket type must be specified.



Dusk to dawn photocell
Available for 120v (**PCL**) or
208-277v (**PCL multi**).


Light Control Options




L3 or L5

GLASS REFRACTOR
Borosilicate glass refractor with IES Type III (**L3**) or Type V (**L5**) light distribution can be specified in most fixtures that don't have an integral refractive lens. The refractor can be retrofitted in existing fixtures without tools or electrical modifications.

Pier Mount




PM06



CFIN
Cast aluminum finial



FIN-08
Cast aluminum finial



FIN-760
Cast aluminum finial